



SALES SPECIFICATION SHEET

FILTRASORB 600 AR+ 12X40

Granular Activated Carbon

Test	Specification		Calgon Carbon Test Method
	Min	Max	
IODINE NUMBER, mg/g	825	-	TM-4,ASTM D4607
MOISTURE (AS PACKAGED), wt%	-	2	TM-1,ASTM D2867
ABRASION NUMBER	75	-	TM-9,AWWA B604
WATER SOLUBLE ASH, wt%	-	1	TM-16
EFFECTIVE SIZE, mm	0.55	0.75	TM-47,ASTM D2862
ASH, wt%	-	10	ASTM D2866, TM-5
12 US MESH [1.70 mm], wt%	-	5	TM-8,ASTM D2862
< 40 US MESH [0.425 mm] (PAN), wt%	-	5	TM-8,ASTM D2862

Typical Properties:

This product complies with the requirements for activated carbon as defined by the Food Chemicals Codex (FCC) (Latest Edition) published by the U.S. Pharmacopeia.

Only products bearing the NSF Mark are Certified to NSF/ANSI 61 - Drinking Water System Components - Health Effects standard. Certified Products will bear the NSF Mark on packing or documentation shipped with the product.

Calgon Carbon Corporation's activated carbon products are continuously being improved and changes may have taken place since this publication went to press. (12124-03/28/2016)